DATA SHEET

Varioflex B

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.







PRODUCT DESCRIPTION

- Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.
- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.

HINTS AND SPECIAL FEATURES

Ideal for applications in difficult terrain.
Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Additional adjustment range on ladder section	0.4 m
Coating	natural

Property	Value
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

PRODUCT VARIANTS

	41936	41938
Additional adjustment range on support section	1.3 m	1.85 m
Length excluding extension	1.8 m	2.35 m
Number of rungs	2 × 6	2 × 8
Transport dimensions	1.850 mm × 600 mm × 140 mm	2.410 mm × 650 mm × 140 mm
Weight	12.5 kg	15.5 kg
Working height	3 m	3.55 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 3



Hook-on tool box
SKU 40920



Ladder holder, lockable
SKU 40998



Tension strap
SKU 40960

SPARE PARTS 2



Plug-in end cap
SKU 800140



User instructions label
SKU 800606

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/11/2026
Subject to change or error.