


Combimaster Plus X

Two ladders in one: combined stepladder and push-up ladder for safe standing.

Product description

- Two ladders in one: combined stepladder and push-up ladder for safe standing.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 265 mm
Standards EN 131 professional	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	

Product variants

SKU 42566	SKU 42568	SKU 42570
Length as trestle 1.75 m	Length as trestle 2.27 m	Length as trestle 2.8 m
Number of rungs 2 × 6	Number of rungs 2 × 8	Number of rungs 2 × 10
Overall length, extended 2.98 m	Overall length, extended 4.1 m	Overall length, extended 4.94 m
Overall length, retracted 1.86 m	Overall length, retracted 2.42 m	Overall length, retracted 2.98 m
Stile depth 58 mm	Stile depth 58 mm	Stile depth 58 mm
Transport dimensions 1.860 mm × 420 mm × 125 mm	Transport dimensions 2.420 mm × 420 mm × 125 mm	Transport dimensions 2.980 mm × 420 mm × 125 mm
Weight 7.9 kg	Weight 10.1 kg	Weight 12.8 kg
Wide crosspiece 0.8 m	Wide crosspiece 0.8 m	Wide crosspiece 0.9 m
Working height 3.8 m	Working height 4.9 m	Working height 5.7 m
SKU 42572	SKU 42574	SKU 42576
Length as trestle 3.33 m	Length as trestle 3.86 m	Length as trestle 4.39 m
Number of rungs	Number of rungs	Number of rungs

2 × 12	2 × 14	2 × 16
Overall length, extended 6.06 m	Overall length, extended 7.19 m	Overall length, extended 8.31 m
Overall length, retracted 3.54 m	Overall length, retracted 4.1 m	Overall length, retracted 4.67 m
Stile depth 73 mm	Stile depth 85 mm	Stile depth 98 mm
Transport dimensions 3.540 mm × 420 mm × 135 mm	Transport dimensions 4.110 mm × 420 mm × 140 mm	Transport dimensions 4.670 mm × 420 mm × 150 mm
Weight 15.3 kg	Weight 20.2 kg	Weight 22 kg
Wide crosspiece 1 m	Wide crosspiece 1.1 m	Wide crosspiece 1.2 m
Working height 6.8 m	Working height 7.9 m	Working height 9 m