

Combimaster DX

The inexpensive alternative for universal use as a push-up ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Base 1,64 m × 0,89 m	Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 265 mm	Standards EN 131 professional	Tread depth 38 mm	Type rung/tread serrated	Warranty 10 years



certification-mark-pf

TÜV-SÜD

Product variants

SKU	SKU	SKU
44868	44870	44872
Length as trestle	Length as trestle	Length as trestle
2.25 m	2.81 m	3.33 m
Number of rungs	Number of rungs	Number of rungs
2 × 8	2 × 10	2 × 12
Overall length, extended	Overall length, extended	Overall length, extended
3.82 m	4.94 m	6.06 m
Overall length, retracted	Overall length, retracted	Overall length, retracted
2.4 m	2.98 m	3.54 m
Stile depth	Stile depth	Stile depth
58 mm	68 mm	73 mm
Transport dimensions	Transport dimensions	Transport dimensions
2.400 mm × 420 mm × 120 mm	2.970 mm × 430 mm × 120 mm	3.530 mm × 430 mm × 130 mm
Weight	Weight	Weight
10 kg	12.3 kg	15.3 kg
Wide crosspiece	Wide crosspiece	Wide crosspiece
0.89 m	0.9 m	1 m
Working height	Working height	Working height
4.9 m	5.7 m	6.8 m



ZARGES

SKU
44874
Length as trestle
3.86 m
Number of rungs
2 × 14
Overall length, extended
6.9 m
Overall length, retracted
4.1 m
Stile depth
85 mm
Transport dimensions
4.090 mm × 430 mm × 135 mm
Weight
18.2 kg
Wide crosspiece
1.1 m
Working height
7.6 m