ZARGES

DATA SHEET

Combimaster DX

The inexpensive alternative for universal use as a push-up ladder and stepladder.



PRODUCT DESCRIPTION

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Base	1,64 m × 0,89 m
Certification	TÜV-SÜD
Coating	natural

Property	Value
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years

PRODUCT VARIANTS

	44868	44870	44872	44874
Length as trestle	2.25 m	2.81 m	3.33 m	3.86 m
Number of rungs	2 × 8	2 × 10	2 × 12	2 × 14
Overall length, extended	3.82 m	4.94 m	6.06 m	6.9 m
Overall length, retracted	2.4 m	2.98 m	3.54 m	4.1 m
Stile depth	58 mm	68 mm	73 mm	85 mm
Transport dimensions	2.400 mm × 420 mm × 120 mm	2.970 mm × 430 mm × 120 mm	3.530 mm × 430 mm × 130 mm	4.090 mm × 430 mm × 135 mm
Weight	10 kg	12.3 kg	15.3 kg	18.2 kg
Wide crosspiece	0.89 m	0.9 m	1 m	1.1 m
Working height	4.9 m	5.7 m	6.8 m	7.6 m

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 9/16/2026
Subject to change or error.