

Combimaster DX

The inexpensive alternative for universal use as a push-up ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|-----------------------|-----------------|
| Base | 1,64 m × 0,89 m |
| Certification | TÜV-SÜD |
| Coating | natural |
| Connection Stile-Rung | flanged |
| Load capacity | max. 150 kg |

| | |
|------------------|---------------------|
| Material | Aluminium |
| Pitch rung/tread | 265 mm |
| Standards | EN 131 professional |
| Tread depth | 38 mm |
| Type rung/tread | serrated |
| Warranty | 10 years |

Product variants

| | 44868 | 44870 | 44872 | 44874 |
|---------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Length as trestle | 2.25 m | 2.81 m | 3.33 m | 3.86 m |
| Number of rungs | 2 × 8 | 2 × 10 | 2 × 12 | 2 × 14 |
| Overall length, extended | 3.82 m | 4.94 m | 6.06 m | 6.9 m |
| Overall length, retracted | 2.4 m | 2.98 m | 3.54 m | 4.1 m |
| Stile depth | 58 mm | 68 mm | 73 mm | 85 mm |
| Transport dimensions | 2.400 mm × 420 mm × 120 mm | 2.970 mm × 430 mm × 120 mm | 3.530 mm × 430 mm × 130 mm | 4.090 mm × 430 mm × 135 mm |
| Weight | 10 kg | 12.3 kg | 15.3 kg | 18.2 kg |
| Wide crosspiece | 0.89 m | 0.9 m | 1 m | 1.1 m |
| Working height | 4.9 m | 5.7 m | 6.8 m | 7.6 m |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/3/2026

Subject to change or error.