ZARGES

DATA SHEET

Roof safety hooks to DIN EN 517

PRODUCT DESCRIPTION

- At least two roof safety hooks are needed in staggered arrangement to ensure secure fastening. For ladders up to 4.20 m in length, two load-bearing roof safety hooks are needed.
- For each additional ladder section of 2.00 / 2.80 m in length, one extra hook is required; for a length of 4.20 m, two extra hooks will be needed.



HINTS AND SPECIAL FEATURES

Supporting safety roof hooks must be fitted centrally on the rafters. Smallest rafter circumference: 60 x 80 mm.

PRODUCT FEATURES

Property	Value
Warranty	Missing translation

PRODUCT VARIANTS

	40969	40490	40970	40967	41399	41386
Colour	Steel, galvanised	Copper-brown	Brick-red	brown	Anthracite grey	Steel, galvanised
Material	Steel, galvanised	Powder-coated steel	Powder-coated steel	Powder-coated steel	Powder-coated steel	Steel, galvanised
Transport dimensions	450 mm × 210 mm × 30 mm	430 mm × 200 mm × 30 mm	450 mm × 210 mm × 30 mm	450 mm × 210 mm × 30 mm	450 mm × 200 mm × 30 mm	430 mm × 190 mm × 30 mm

	40969	40490	40970	40967	41399	41386
Version	for pantiles and double depression interlocking ti	for pantiles and double depression interlocking ti	for pantiles and double depression interlocking ti	for pantiles and double depression interlocking ti	for pantiles and double depression interlocking ti	for plain tiles
Weight	1.2 kg	1.1 kg	1.2 kg	1.2 kg	1.2 kg	1 kg

	40492	41387	41388	41389
Colour	Copper-brown	Brick-red	brown	Anthracite grey
Material	Powder-coated steel	Powder-coated steel	Powder-coated steel	Powder-coated steel
Transport dimensions	430 mm × 200 mm × 30 mm	420 mm × 200 mm × 30 mm	430 mm × 190 mm × 30 mm	430 mm × 190 mm × 30 mm
Version	for plain tiles	for plain tiles	for plain tiles	for plain tiles
Weight	1.2 kg	1 kg	1 kg	1 kg

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/11/2026
Subject to change or error.