

# Roof safety hooks to DIN

## EN 517

### Product description

- At least two roof safety hooks are needed in staggered arrangement to ensure secure fastening. For ladders up to 4.20 m in length, two load-bearing roof safety hooks are needed.
- For each additional ladder section of 2.00 / 2.80 m in length, one extra hook is required; for a length of 4.20 m, two extra hooks will be needed.



### Hints and special features

Supporting safety roof hooks must be fitted centrally on the rafters. Smallest rafter circumference: 60 x 80 mm.

### Product features

Warranty	Missing translation
----------	---------------------

### Product variants

	40969	40490	40970	40967	41399	41386
Colour	Steel, galvanised	Copper-brown	Brick-red	brown	Anthracite grey	Steel, galvanised
Material	Steel, galvanised	Powder-coated steel	Powder-coated steel	Powder-coated steel	Powder-coated steel	Steel, galvanised
Transport dimensions	450 mm × 210 mm × 30 mm	430 mm × 200 mm × 30 mm	450 mm × 210 mm × 30 mm	450 mm × 210 mm × 30 mm	450 mm × 200 mm × 30 mm	430 mm × 190 mm × 30 mm



	40969	40490	40970	40967	41399	41386
Version	for pantiles and double depression interlocking ti	for plain tiles				
Weight	1.2 kg	1.1 kg	1.2 kg	1.2 kg	1.2 kg	1 kg

	40492	41387	41388	41389
Colour	Copper-brown	Brick-red	brown	Anthracite grey
Material	Powder-coated steel	Powder-coated steel	Powder-coated steel	Powder-coated steel
Transport dimensions	430 mm x 200 mm x 30 mm	420 mm x 200 mm x 30 mm	430 mm x 190 mm x 30 mm	430 mm x 190 mm x 30 mm
Version	for plain tiles	for plain tiles	for plain tiles	for plain tiles
Weight	1.2 kg	1 kg	1 kg	1 kg

ZARGES GmbH	Tel: +49 (0)881-687-100	www.zarges.com
Zargesstraße 7	Fax: +49 (0)881-687-500	Effective 5/13/2026
82362 Weilheim	zarges@zarges.de	Subject to change or error.