

Mobile access steps with platform, single-sided access, with light-alloy treads and platform

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.



Product description

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

Coating	natural
Connection Stile-Rung	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	240 mm
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Tread depth	200 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	41971	41972	41973	41974	41975	41976
Base	0,77 m × 1,27 m	0,82 m × 1,45 m	0,87 m × 1,63 m	0,93 m × 1,81 m	0,98 m × 1,99 m	1,03 m × 2,17 m
Number of rungs, incl. platform	3	4	5	6	7	8
Platform height	0.72 m	0.96 m	1.2 m	1.44 m	1.68 m	1.92 m
Transport dimensions	1.180 mm × 820 mm × 330 mm	1.350 mm × 820 mm × 400 mm	1.380 mm × 950 mm × 420 mm	1.850 mm × 1.000 mm × 330 mm	1.920 mm × 1.060 mm × 410 mm	2.220 mm × 1.030 mm × 360 mm
Weight	28.5 kg	31.8 kg	35 kg	38.4 kg	41.8 kg	45.6 kg
Working height	2.7 m	2.95 m	3.2 m	3.45 m	3.7 m	3.9 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/3/2026

Subject to change or error.