



## Mobile access steps with platform, single-sided access, with steel open-grid treads and platform

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.

### Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

### Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

### Product features



Coating	natural
Connection Stile-Rung	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminum/steel, galvanised
Pitch rung/tread	240 mm
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Tread depth	200 mm
Type rung/tread	Open-grid surface
Warranty	10 years

## Product variants

	41951	41952	41953	41954	41955	41956
Base	0,77 m × 1,27 m	0,82 m × 1,45 m	0,87 m × 1,63 m	0,93 m × 1,81 m	0,98 m × 1,99 m	1,03 m × 2,17 m
Number of rungs, incl. platform	3	4	5	6	7	8
Platform height	0.72 m	0.96 m	1.2 m	1.44 m	1.68 m	1.92 m
Transport dimensions	1.150 mm × 780 mm × 350 mm	1.350 mm × 830 mm × 410 mm	1.500 mm × 890 mm × 410 mm	1.820 mm × 930 mm × 350 mm	1.920 mm × 990 mm × 350 mm	2.220 mm × 1.130 mm × 350 mm
Weight	41.5 kg	47.5 kg	53.6 kg	59.7 kg	66 kg	72.9 kg
Working height	2.7 m	2.95 m	3.2 m	3.45 m	3.7 m	3.9 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/3/2026

Subject to change or error.