

Mobile access steps with platform, double-sided access, with light-alloy treads and platform

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.



Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

Coating	natural
Connection Stile-Rung	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	240 mm
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Tread depth	200 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	41981	41982	41983	41984	41985	41986
Base	0,77 m × 1,51 m	0,82 m × 1,79 m	0,87 m × 2,06 m	0,93 m × 2,34 m	0,98 m × 2,62 m	1,03 m × 2,9 m
Number of rungs, incl. platform	2 × 3	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8
Number of treads	3	4	5	6	7	8
Platform height	0.72 m	0.96 m	1.2 m	1.44 m	1.68 m	1.92 m
Transport dimensions	1.300 mm × 820 mm × 470 mm	1.980 mm × 880 mm × 300 mm	1.850 mm × 940 mm × 440 mm	2.200 mm × 1.020 mm × 410 mm	2.250 mm × 1.060 mm × 410 mm	2.820 mm × 1.120 mm × 410 mm
Weight	31.2 kg	36 kg	41 kg	46.2 kg	51.7 kg	57.5 kg



	41981	41982	41983	41984	41985	41986
Working height	2.7 m	2.95 m	3.2 m	3.45 m	3.7 m	3.9 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/4/2026

Subject to change or error.