

ZAP Safemaster Plus S

The perfect solution for picking tasks on shelves.
Large storage surface, easy to roll, compact when folded.

Product description

- The perfect solution for picking tasks on shelves. Large storage surface, easy to roll, compact when folded.
- Access section with horizontal stabiliser bar, support section with chassis beam, wheels with locking mechanism (diameter 160 mm).
- Easy folding of the ladder for space-saving storage due to hinges in both diagonal braces.
- Aluminium work platform, approx. 600 x 630 mm, with safety guard rail on three sides.
- Narrow chassis. The chassis width is reduced to a minimum through additional ballasting.
- Large storage and retrieval tray.



Hints and special features

Safe standing thanks to large, 600 × 630 mm aluminium platform with guardrail.

Complies with EN 131-7

Product features

Load capacity	max. 150 kg
Platform length	630 mm
Platform material	Aluminium ribbed plate

Platform width	600 mm
Standards	EN 131-7
Tray	Aluminium
Tread depth	80 mm
Type rung/tread	Safer Step
Warranty	10 years

Product variants

	41201	41202	41203	41204	41205	41207
Base	1,25 m × 1,09 m	1,4 m × 1,09 m	1,5 m × 1,29 m	1,65 m × 1,29 m	1,8 m × 1,69 m	2,05 m × 1,89 m
Chassis-beam width	1.09 m	1.09 m	1.29 m	1.29 m	1.69 m	1.89 m
Height including railing	2 m	2.3 m	2.6 m	2.8 m	3.1 m	3.6 m
Number of rungs, incl. platform	4	5	6	7	8	10
Platform height	1 m	1.3 m	1.6 m	1.8 m	2.1 m	2.6 m
Transport dimensions	2.645 mm × 730 mm × 216 mm	2.920 mm × 720 mm × 250 mm	3.212 mm × 650 mm × 225 mm	3.492 mm × 650 mm × 226 mm	3.772 mm × 650 mm × 227 mm	4.332 mm × 650 mm × 226 mm
Weight	42 kg	43 kg	47 kg	50.6 kg	55 kg	61 kg
Wide crosspiece	–	–	1 m	1 m	1 m	1 m
Working height	3 m	3.3 m	3.6 m	3.8 m	4.1 m	4.6 m

	41209
Base	2,3 m × 1,89 m
Chassis-beam width	1.89 m
Height including railing	4.1 m
Number of rungs, incl. platform	12



	41209
Platform height	3.1 m
Transport dimensions	4.892 mm × 650 mm × 230 mm
Weight	65.8 kg
Wide crosspiece	1 m
Working height	5.1 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/16/2026

Subject to change or error.