

# Single-section fixed ladder systems, access height of up to 10 m, V4A stainless steel

Stationary access to buildings and machinery up to a height of 10 m, also suitable and approved for use as an escape route.

## Product description

- For stationary mounting, on buildings either for maintenance in accordance with DIN 18 799-1 or as an emergency ladder system in accordance with DIN 14 094-1 or as machine access steps in accordance with DIN EN ISO 14 122-4.
- Back cage as safety system, complies with any standard.
- Arrester rail as a safety system in accordance with DIN EN 353-1, DIN 18 799-1 and DIN EN ISO 14 122-4, can be supplied as a single-section fixed ladder even with climbing heights of over 10 m.
- Ladder width: 520 mm.
- Wall brackets with various wall distances up to 600 mm can be selected.
- The distance between the wall brackets is max. 2.00 m. But each ladder section must be mounted with at least 2 wall brackets.
- Material: Stainless steel, 1.4571 (AISI 316 Ti) in accordance with EN 10088-2, corrosion class C4
- Safety barriers, access protection and platforms can



be selected to suit individual requirements.

- On request, we can also produce fixed-ladders that differ from the standard specifications.

## Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.

The prices for single-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, incl. back cage in accordance with DIN 18 799-1. In the case of other requirements, please use our planning system for fixed ladders.

## Product features

Material	stainless steel
Warranty	10 years

## Product variants

	58448	58457	58465	58474	58485	58496
Overall length incl. stile	5.9 m	6.7 m	7.6 m	8.5 m	9.6 m	10.7 m
access height	4.8 m	5.6 m	6.5 m	7.4 m	8.5 m	9.6 m

ZARGES GmbH Zargesstraße 7 82362 Weilheim	Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 zarges@zarges.de	www.zarges.com Effective 6/15/2026 Subject to change or error.
---	--	--