

# Multi-section fixed ladder systems, natural aluminium

Multi-section access solution with crossover platform for buildings and machinery.

## Product description

- For permanent installation to BGV D 36 and DIN 18 799-1, DIN 14 094-1 and EN ISO 14 122-4.
- With back guards.
- Ladder width: 520 mm.
- Wall brackets with various wall distances up to 600 mm can be selected.
- The distance between the wall brackets is max. 2.00 m. But each ladder section must be mounted with at least 2 wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- On request, we can also produce fixed-ladders that differ from the standard specifications.



## Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.

The prices for double-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, crossover platform, incl. back cage in accordance with DIN 18 799-1. In the case of other requirements, please use our planning system for

fixed ladders.

## Product features

Material	Natural aluminium
Warranty	10 years

## Product variants

	58607	58618	58626	58638	58649	58657
Overall length incl. stile	11.8 m	12.9 m	13.7 m	14.9 m	16 m	16.8 m
access height	10.7 m	11.8 m	12.6 m	13.8 m	14.9 m	15.7 m

	58668	58680	58691
Overall length incl. stile	17.9 m	19.1 m	20.2 m
access height	16.8 m	18 m	19.1 m

ZARGES GmbH	Tel: +49 (0)881-687-100	www.zarges.com
Zargesstraße 7	Fax: +49 (0)881-687-500	Effective 5/2/2026
82362 Weilheim	zarges@zarges.de	Subject to change or error.