

Well cover, square, with ventilation chimney

Product description

- Lid made from sheet metal, 2.5 mm thick, elevated in the centre, with internal transverse bracing
- From 800 × 800 mm or Ø 800 mm with gas pressure springs.
- Self-locking fastener, locking mechanism can only be disengaged by hand.
- Frame prepared for setting in concrete and attachment with rawlplugs.
- EPDM seal on the underside of the lid



Product features

Shape	Square with a ventilation chimney
-------	-----------------------------------

Product variants

	47110	47111	47112	47118	47119	47120
Inside shaft length	625 mm	800 mm	1000 mm	625 mm	800 mm	1000 mm
Inside shaft size	625mm × 625mm	800mm × 800mm	1.000mm × 1.000mm	625mm × 625mm	800mm × 800mm	1.000mm × 1.000mm
Inside shaft width	625 mm	800 mm	1000 mm	625 mm	800 mm	1000 mm
Material	Steel, galvanised	Steel, galvanised	Steel, galvanised	Steel, galvanised	Steel, galvanised	Galvanised steel
Outside dimensions max. L x W x H	745 mm × 745 mm	920 mm × 920 mm	1.120 mm × 1.120 mm	745 mm × 745 mm	920 mm × 920 mm	1.120 mm × 1.120 mm
Transport dimensions	740 mm × 740 mm × 460 mm	920 mm × 920 mm × 460 mm	1.120 mm × 1.120 mm × 460 mm	750 mm × 750 mm × 480 mm	920 mm × 920 mm × 480 mm	1.120 mm × 1.120 mm × 480 mm



	47110	47111	47112	47118	47119	47120
Version	without insulation	without insulation	without insulation	with insulation	with insulation	with insulation

	47114	47115	47180	47116	47117	47122
Inside shaft length	625 mm	800 mm	1000 mm	1000 mm	1200 mm	625 mm
Inside shaft size	625mm x 625mm	800mm x 800mm	1.000mm x 800mm	1.000mm x 1.000mm	1.200mm x 1.200mm	625mm x 625mm
Inside shaft width	625 mm	800 mm	800 mm	1000 mm	1200 mm	625 mm
Material	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel
Outside dimensions max. L x W x H	745 mm x 745 mm	920 mm x 920 mm	1.120 mm x 920 mm	1.120 mm x 1.120 mm	1.320 mm x 1.320 mm	745 mm x 745 mm
Transport dimensions	740 mm x 740 mm x 460 mm	920 mm x 920 mm x 460 mm	1.120 mm x 920 mm x 400 mm	1.120 mm x 1.120 mm x 460 mm	1.320 mm x 1.320 mm x 460 mm	740 mm x 740 mm x 480 mm
Version	without insulation	without insulation	without insulation	without insulation	without insulation	with insulation

	47123	47190	47124	47125
Inside shaft length	800 mm	1000 mm	1000 mm	1200 mm
Inside shaft size	800mm x 800mm	1.000mm x 800mm	1.000mm x 1.000mm	1.200mm x 1.200mm
Inside shaft width	800 mm	800 mm	1000 mm	1200 mm
Material	stainless steel	stainless steel	stainless steel	stainless steel
Outside dimensions max. L x W x H	920 mm x 920 mm	1.120 mm x 920 mm	1.120 mm x 1.120 mm	1.320 mm x 1.320 mm
Transport dimensions	920 mm x 920 mm x 480 mm	1.120 mm x 920 mm x 460 mm	1.120 mm x 1.120 mm x 480 mm	1.320 mm x 1.320 mm x 480 mm
Version	with insulation	with insulation	with insulation	with insulation

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/14/2026

Subject to change or error.