

Shaft cover with overlapping cover, square

Product description

- Lid made from sheet metal, 2.5 mm thick, elevated in the centre, with internal transverse bracing
- From 800 × 800 mm or Ø 800 mm with gas pressure springs.
- Self-locking fastener, locking mechanism can only be disengaged by hand.
- Frame prepared for setting in concrete and attachment with rawlplugs.



Product features

| | |
|-------|--------------------------------------|
| Shape | Square without a ventilation chimney |
|-------|--------------------------------------|

Product variants

| | 47140 | 47141 | 47142 | 47148 | 47149 | 47150 |
|-----------------------------------|--------------------------|--------------------------|------------------------------|--------------------------|--------------------------|------------------------------|
| Inside shaft length | 625 mm | 800 mm | 1000 mm | 625 mm | 800 mm | 1000 mm |
| Inside shaft size | 625mm × 625mm | 800mm × 800mm | 1.000mm × 1.000mm | 625mm × 625mm | 800mm × 800mm | 1.000mm × 1.000mm |
| Inside shaft width | 625 mm | 800 mm | 1000 mm | 625 mm | 800 mm | 1000 mm |
| Material | Steel, galvanised | Steel, galvanised | Steel, galvanised | Steel, galvanised | Steel, galvanised | Steel, galvanised |
| Outside dimensions max. L x W x H | 745 mm × 745 mm | 920 mm × 920 mm | 1.120 mm × 1.120 mm | 745 mm × 745 mm | 920 mm × 920 mm | 1.120 mm × 1.120 mm |
| Transport dimensions | 740 mm × 740 mm × 200 mm | 920 mm × 920 mm × 200 mm | 1.120 mm × 1.120 mm × 200 mm | 740 mm × 740 mm × 200 mm | 920 mm × 920 mm × 200 mm | 1.120 mm × 1.120 mm × 200 mm |
| Version | without insulation | without insulation | without insulation | with insulation | with insulation | with insulation |



| | 47144 | 47145 | 47181 | 47146 | 47147 | 47152 |
|-----------------------------------|--------------------------|--------------------------|----------------------------|------------------------------|------------------------------|--------------------------|
| Inside shaft length | 625 mm | 800 mm | 1000 mm | 1000 mm | 1200 mm | 625 mm |
| Inside shaft size | 625mm × 625mm | 800mm × 800mm | 1.000mm × 800mm | 1.000mm × 1.000mm | 1.200mm × 1.200mm | 625mm × 625mm |
| Inside shaft width | 625 mm | 800 mm | 800 mm | 1000 mm | 1200 mm | 625 mm |
| Material | stainless steel | stainless steel | stainless steel | stainless steel | stainless steel | stainless steel |
| Outside dimensions max. L x W x H | 745 mm × 745 mm | 920 mm × 920 mm | 1.120 mm × 820 mm | 1.120 mm × 1.120 mm | 1.320 mm × 1.320 mm | 745 mm × 745 mm |
| Transport dimensions | 740 mm × 740 mm × 200 mm | 920 mm × 920 mm × 200 mm | 1.120 mm × 820 mm × 200 mm | 1.120 mm × 1.120 mm × 200 mm | 1.320 mm × 1.320 mm × 200 mm | 745 mm × 745 mm × 200 mm |
| Version | without insulation | without insulation | without insulation | without insulation | without insulation | with insulation |

| | 47153 | 47191 | 47154 | 47155 |
|-----------------------------------|--------------------------|----------------------------|------------------------------|------------------------------|
| Inside shaft length | 800 mm | 1000 mm | 1000 mm | 1200 mm |
| Inside shaft size | 800mm × 800mm | 1.000mm × 800mm | 1.000mm × 1.000mm | 1.200mm × 1.200mm |
| Inside shaft width | 800 mm | 800 mm | 1000 mm | 1200 mm |
| Material | stainless steel | stainless steel | stainless steel | – |
| Outside dimensions max. L x W x H | 920 mm × 920 mm | 1.120 mm × 920 mm | 1.120 mm × 1.120 mm | 1.320 mm × 1.320 mm |
| Transport dimensions | 920 mm × 920 mm × 200 mm | 1.120 mm × 920 mm × 280 mm | 1.120 mm × 1.120 mm × 200 mm | 1.320 mm × 1.320 mm × 200 mm |
| Version | with insulation | with insulation | with insulation | with insulation |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/30/2026

Subject to change or error.