



Stainless-steel shaft covers with cover trough

Shaft covers that can be walked or driven on, with customisable inner and outer surface.

Product description

- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapering section design, therefore easy to open. No sticking.
- Easy to open, no jamming.
- Odour-tight and impervious to surface water.
- Load with choice of surface: test force 125 kN (=12.5 t), only after cover trough has been filled by customer with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.
- Trough depth 80 mm (of which 40 mm covered with construction steel grating and 40 mm free area)



Product features

Design height	90 mm
Trough depth	80 mm

Product variants

	47060	47061	47062	47064	47065	47067
Inside shaft length	300 mm	450 mm	500 mm	600 mm	635 mm	800 mm
Inside shaft size	300mm × 300mm	450mm × 450mm	500mm × 500mm	600mm × 600mm	635mm × 635mm	800mm × 800mm
Inside shaft width	300 mm	450 mm	500 mm	600 mm	635 mm	800 mm
Outside dimensions max. L x W x H	420 mm × 420 mm	570 mm × 570 mm	620 mm × 620 mm	720 mm × 720 mm	755 mm × 755 mm	920 mm × 920 mm
Transport dimensions	420 mm × 420 mm × 90 mm	570 mm × 570 mm × 90 mm	620 mm × 620 mm × 90 mm	720 mm × 720 mm × 90 mm	750 mm × 750 mm × 90 mm	920 mm × 920 mm × 90 mm

	47070
Inside shaft length	1000 mm
Inside shaft size	1.000mm × 1.000mm
Inside shaft width	1000 mm
Outside dimensions max. L x W x H	1.120 mm × 1.120 mm
Transport dimensions	1.120 mm × 1.120 mm × 90 mm

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.