


Mobile access steps with platform

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.



Product description

- Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Individually adjustable platform lengths.
- Cantilever platform available for bridging obstacles.
- Chassis available in a non-static version as an option.
- Narrow chassis. The chassis width is reduced to a minimum through additional ballasting.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and



guardrails which can be removed without tools.

- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

Product features

Load capacity	max. 300 kg
Max. load per tread	150 kg
Platform length	600 mm
Standards	NF EN ISO 14122-4
Warranty	10 years

Product variants

	40255764	40255766	40255768	40255770	40255772	40255774
Chassis width	1020 mm	1020 mm	1020 mm	1220 mm	1220 mm	1220 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	5	7	9	11	12	14
Overall span	1698 mm	2128 mm	2558 mm	3017 mm	3447 mm	3877 mm



	40255764	40255766	40255768	40255770	40255772	40255774
Tread width	600 mm	600 mm	600 mm	600 mm	600 mm	600 mm
Vertical height	1070 mm	1500 mm	1930 mm	2360 mm	2790 mm	3220 mm

	40255776	40255778	40255780	40255784	40255786	40255788
Chassis width	1220 mm	1420 mm	1420 mm	1220 mm	1220 mm	1220 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	16	18	20	5	7	9
Overall span	4307 mm	4737 mm	5167 mm	1698 mm	2128 mm	2558 mm
Tread width	600 mm	600 mm	600 mm	800 mm	800 mm	800 mm
Vertical height	3650 mm	4080 mm	4510 mm	1070 mm	1500 mm	1930 mm

	40255790	40255792	40255794	40255796	40255798	40255800
Chassis width	1220 mm	1220 mm	1420 mm	1420 mm	1420 mm	1620 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	11	12	14	16	18	20
Overall span	3017 mm	3447 mm	3877 mm	4307 mm	4737 mm	5167 mm
Tread width	800 mm	800 mm	800 mm	800 mm	800 mm	800 mm
Vertical height	2360 mm	2790 mm	3220 mm	3650 mm	4080 mm	4510 mm

	40255804	40255806	40255808	40255810	40255812	40255814
Chassis width	1420 mm	1420 mm	1420 mm	1420 mm	1420 mm	1420 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	5	7	9	11	12	14
Overall span	1698 mm	2128 mm	2558 mm	3017 mm	3447 mm	3877 mm
Tread width	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm
Vertical height	1070 mm	1500 mm	1930 mm	2360 mm	2790 mm	3220 mm



	40255816	40255818	40255820	40255704	40255706	40255708
Chassis width	1420 mm	1420 mm	1620 mm	1220 mm	1420 mm	1820 mm
Inclination	45 °	45 °	45 °	60 °	60 °	60 °
Number of treads	16	18	20	5	7	9
Overall span	4307 mm	4737 mm	5167 mm	1453 mm	1707 mm	1996 mm
Tread width	1000 mm	1000 mm	1000 mm	600 mm	600 mm	600 mm
Vertical height	3650 mm	4080 mm	4510 mm	1250 mm	1750 mm	2250 mm

	40255710	40255712	40255714	40255716	40255724	40255726
Chassis width	1620 mm	1620 mm	1620 mm	1620 mm	1220 mm	1220 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	11	12	14	17	5	7
Overall span	2285 mm	2607 mm	2896 mm	3185 mm	1453 mm	1707 mm
Tread width	600 mm	600 mm	600 mm	600 mm	800 mm	800 mm
Vertical height	2750 mm	3250 mm	3750 mm	4250 mm	1250 mm	1750 mm

	40255728	40255730	40255732	40255734	40255736	40255744
Chassis width	1620 mm	1420 mm	1420 mm	1420 mm	1620 mm	1420 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	9	11	12	14	17	5
Overall span	1996 mm	2285 mm	2607 mm	2896 mm	3185 mm	1453 mm
Tread width	800 mm	800 mm	800 mm	800 mm	800 mm	1000 mm
Vertical height	2250 mm	2750 mm	3250 mm	3750 mm	4250 mm	1250 mm

	40255746	40255748	40255750	40255752	40255754	40255756
Chassis width	1420 mm	1420 mm	1420 mm	1420 mm	1420 mm	1620 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	7	9	11	12	14	17



	40255746	40255748	40255750	40255752	40255754	40255756
Overall span	1707 mm	1996 mm	2285 mm	2607 mm	2720 mm	3207 mm
Tread width	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm
Vertical height	1750 mm	2250 mm	2750 mm	3250 mm	3750 mm	4250 mm

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/6/2026

Subject to change or error.