

## Platform steps

Compact work platform with easy-going steps. Choice of stationary or mobile version (for moving quickly to another working position). Ideal for work over long periods, even with tools.

### Product description

- Compact work platform with easy access. Ideal for extended work sessions, even when using tools.



### Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.



### Product features

Load capacity	max. 300 kg
Max. load per tread	150 kg
Platform length	400 mm
Warranty	10 years

### Product variants



	40855520	40855521	40855522	40855523	40855524	40855525
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	2	3	4	5	2	3
Overall span	951 mm	1151 mm	1351 mm	1541 mm	951 mm	1151 mm
Tread width	600 mm	600 mm	600 mm	600 mm	800 mm	800 mm
Vertical height	400 mm	600 mm	800 mm	990 mm	400 mm	600 mm

	40855526	40855527	40855528	40855529	40855530	40855531
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	4	5	2	3	4	5
Overall span	1351 mm	1541 mm	951 mm	1151 mm	1351 mm	1541 mm
Tread width	800 mm	800 mm	1000 mm	1000 mm	1000 mm	1000 mm
Vertical height	800 mm	990 mm	400 mm	600 mm	800 mm	990 mm

	40855540	40855541	40855542	40855544	40855545	40855546
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	2	3	4	2	3	4
Overall span	864 mm	1008 mm	1147 mm	864 mm	1008 mm	1147 mm
Tread width	600 mm	600 mm	600 mm	800 mm	800 mm	800 mm
Vertical height	500 mm	750 mm	990 mm	500 mm	750 mm	990 mm

	40855548	40855549	40855550
Inclination	60 °	60 °	60 °
Number of treads	2	3	4
Overall span	864 mm	1008 mm	1147 mm
Tread width	1000 mm	1000 mm	1000 mm
Vertical height	500 mm	750 mm	990 mm



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/20/2026

Subject to change or error.