

## R13step S

Stable footing even in wet or oily conditions: on R13 treads when going up and down, as well as on the extra-wide platform.

### Product description

- Stable footing even in wet or oily conditions: on R13 treads when going up and down, as well as on the extra-wide platform.
- The widest platform in its class, featuring an R13-rated surface for a non-slip, comfortable stance even during extended use.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- Clean hands thanks to wear-resistant anodised stiles.
- The 280 mm-high step provides the greatest working height in its class.
- High-strength Perlon belts prevent splay, fitted on all models of 5 rungs or more.
- Robust design: flanged step-stile connection with a platform and extruded aluminum profiles.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Platform and treads with R13 surface.

Complies with EN 131 Professional.

## Product features

Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	68 mm
Stile depth	58 mm
Stile depth steps/back stay	68mm / 58mm
Tray	Aluminium
Tread depth	80 mm
Type rung/tread	R13 tread
Warranty	10 years

## Product variants

	41636	41637	41638	41639	41640	41641
Anti splay	–	–	Belt strap	Belt strap	Belt strap	Belt strap
Base	0,74 m × 0,49 m	0,92 m × 0,52 m	1,09 m × 0,55 m	1,25 m × 0,58 m	1,42 m × 0,61 m	1,58 m × 0,64 m
Number of rungs, incl. platform	3	4	5	6	7	8
Overall base width	0.49 m	0.52 m	0.55 m	0.58 m	0.61 m	0.64 m
Overall length	1.59 m	1.87 m	2.15 m	2.43 m	2.71 m	2.99 m
Platform height	0.8 m	1.06 m	1.33 m	1.59 m	1.85 m	2.12 m
Transport dimensions	approx. 1.590 mm × approx. 490 mm × approx. 170 mm	approx. 1.870 mm × approx. 520 mm × approx. 170 mm	approx. 2.150 mm × approx. 550 mm × approx. 170 mm	approx. 2.430 mm × approx. 580 mm × approx. 170 mm	approx. 2.710 mm × approx. 610 mm × approx. 170 mm	approx. 2.990 mm × approx. 640 mm × approx. 170 mm
Weight	8.3 kg	9.8 kg	10.5 kg	11.5 kg	12.3 kg	12.8 kg
Working height	2.8 m	3.1 m	3.35 m	3.6 m	3.85 m	4.15 m

	41642
Anti splay	Belt strap
Base	1,9 m × 0,7 m
Number of rungs, incl. platform	10
Overall base width	0.7 m
Overall length	3.55 m
Platform height	2.64 m
Transport dimensions	approx. 3.550 mm × approx. 700 mm × approx. 170 mm
Weight	16.1 kg
Working height	4.65 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 5/29/2026

Subject to change or error.