

R13step S

Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.

Product description

- Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.
- Large platform with R13 surface that allows personnel to stand safely and comfortably even when working for extended periods.
- Spacious aluminium storage tray for material and tools.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Maximum working heights thanks to 280mm high access.
- High-strength Perlon belts prevent splay, fitted on all models of 5 rungs or more.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Platform and treads with R13 surface.

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	anodised

Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	68 mm
Stile depth	58 mm
Stile depth steps/back stay	68mm / 58mm
Tray	Aluminium
Tread depth	80 mm
Type rung/tread	R13 tread
Warranty	10 years

Product variants

	41636	41637	41638	41639	41640	41641
Anti splay	–	–	Belt strap	Belt strap	Belt strap	Belt strap
Base	0,74 m × 0,49 m	0,92 m × 0,52 m	1,09 m × 0,55 m	1,25 m × 0,58 m	1,42 m × 0,61 m	1,58 m × 0,64 m
Number of rungs, incl. platform	3	4	5	6	7	8
Overall base width	0.49 m	0.52 m	0.55 m	0.58 m	0.61 m	0.64 m
Overall length	1.59 m	1.87 m	2.15 m	2.43 m	2.71 m	2.99 m
Platform height	0.8 m	1.06 m	1.33 m	1.59 m	1.85 m	2.12 m



	41636	41637	41638	41639	41640	41641
Transport dimensions	approx. 1.590 mm × approx. 490 mm × approx. 170 mm	approx. 1.870 mm × approx. 520 mm × approx. 170 mm	approx. 2.150 mm × approx. 550 mm × approx. 170 mm	approx. 2.430 mm × approx. 580 mm × approx. 170 mm	approx. 2.710 mm × approx. 610 mm × approx. 170 mm	approx. 2.990 mm × approx. 640 mm × approx. 170 mm
Weight	8.3 kg	9.8 kg	10.5 kg	11.5 kg	12.3 kg	12.8 kg
Working height	2.8 m	3.1 m	3.35 m	3.6 m	3.85 m	4.15 m

	41642
Anti splay	Belt strap
Base	1,9 m × 0,7 m
Number of rungs, incl. platform	10
Overall base width	0.7 m
Overall length	3.55 m
Platform height	2.64 m
Transport dimensions	approx. 3.550 mm × approx. 700 mm × approx. 170 mm
Weight	16.1 kg
Working height	4.65 m

ZARGES GmbH Zargesstraße 7 82362 Weilheim	Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 zarges@zarges.de	www.zarges.com Effective 4/14/2026 Subject to change or error.
---	--	--