

## R13step B

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

### Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- Clean hands thanks to wear-resistant anodised stiles.
- Sturdy hinges made of die-cast aluminum.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- The 280 mm-high step provides the greatest working height in its class.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Robust design: flanged step-rail connection with extruded aluminum profiles.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti splay	Belt strap
Certification	TÜV-SÜD

Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	68 mm
Tread depth	80 mm
Type rung/tread	R13 tread
Warranty	10 years

## Product variants

	41549	41551	41553	41555	41557	41559
Base	0,79 m × 0,44 m	0,98 m × 0,47 m	1,18 m × 0,5 m	1,38 m × 0,53 m	1,57 m × 0,56 m	1,77 m × 0,59 m
Number of treads	2 × 3	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8
Overall base width	0.44 m	0.47 m	0.5 m	0.53 m	0.56 m	0.59 m
Overall length	0.88 m	1.15 m	1.44 m	1.72 m	1.99 m	2.27 m
Transport dimensions	approx. 880 mm × approx. 450 mm × approx. 220 mm	approx. 1.155 mm × approx. 475 mm × approx. 220 mm	approx. 1.440 mm × approx. 500 mm × approx. 220 mm	approx. 1.750 mm × approx. 530 mm × approx. 220 mm	approx. 2.000 mm × approx. 560 mm × approx. 220 mm	approx. 2.280 mm × approx. 590 mm × approx. 220 mm
Vertical ladder height	0.8 m	1.06 m	1.32 m	1.58 m	1.84 m	2.1 m
Weight	5.1 kg	6.6 kg	8.3 kg	9.3 kg	11 kg	12.7 kg
Working height	2.3 m	2.55 m	2.8 m	3.05 m	3.3 m	3.6 m



	41561	41563	41565	41567
Base	2,16 m × 0,65 m	2,55 m × 0,71 m	2,95 m × 0,76 m	3,34 m × 0,82 m
Number of treads	2 × 10	2 × 12	2 × 14	2 × 16
Overall base width	0.65 m	0.71 m	0.77 m	0.83 m
Overall length	2.83 m	3.39 m	3.95 m	4.51 m
Transport dimensions	approx. 2.840 mm × approx. 650 mm × approx. 220 mm	approx. 3.390 mm × approx. 710 mm × approx. 220 mm	approx. 3.950 mm × approx. 760 mm × approx. 220 mm	approx. 4.510 mm × approx. 820 mm × approx. 220 mm
Vertical ladder height	2.62 m	3.15 m	3.67 m	4.21 m
Weight	16.3 kg	20 kg	24.1 kg	28.5 kg
Working height	4.15 m	4.65 m	5.2 m	5.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 7/1/2026

Subject to change or error.