

Two-axle fuelling platform without fuelling equipment

Thanks to its gentle ascent, the two-axle fuelling platform makes it possible to carry out refuelling from any tread.

Product description

- Platform height: 1.60 metres
- This product can be ordered with towing eye or ball coupling on its tow bar depending on the towing vehicle used.
- This product allows personnel to work at heights from approx. 2.90 to 3.50 m.
- A platform (450 x 650 mm) optimised for secure footing offers enough space for refuelling to be performed ergonomically.
- The treads and platform are fitted with R13 anti-slip safety panels that allow water to drain easily, offering an extremely high level of safety.
- The 415 mm pneumatic tyres in combination with a tow bar allow for towing speeds of up to 30 km/h.
- Our platforms comply with the European standards EN 12312-5 and EN 1915-1.

Hints and special features

No fuelling equipment is included for this product variant. However, the same product is also available with fuelling equipment, either already or not yet primed.





Standards used: DIN EN 1915 - General requirements
Part 1 - Basic safety requirements
Part 2 - Stability and strength requirements
DIN EN 12312 - Aircraft ground support equipment
Part 5 - Aircraft fuelling equipment
Part 8 - Maintenance stairs and platforms

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/10/2026

Subject to change or error.