

Everest 3DE

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	natural
Connection Stile-Rung	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg
Material	Aluminium

Pitch rung/tread 265 mm

Standards EN 131 professional

Tread depth 38 mm

Type rung/tread serrated

Warranty 10 years

Product variants

	44851	44852	44853	44854
Number of rungs	3 × 8	3 × 10	3 × 12	3 × 14
Overall length, extended	5.25 m	6.65 m	8.33 m	9.45 m
Overall length, retracted	2.41 m	2.97 m	3.53 m	4.09 m
Stile depth	68 mm	73 mm	85 mm	85 mm
Transport dimensions	2.410 mm × 500 mm × 170 mm	2.970 mm × 500 mm × 190 mm	3.530 mm × 500 mm × 190 mm	4.090 mm × 500 mm × 190 mm
Weight	15.3 kg	19.2 kg	24.2 kg	36 kg
Wide crosspiece	0.9 m	1.1 m	1.2 m	1.2 m
Working height	5.95 m	7.25 m	8.8 m	9.9 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.