

Everest 3DE

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 265 mm	Standards EN 131 professional	Tread depth 38 mm	Type rung/tread serrated	Warranty 10 years



Product variants

SKU 44851	SKU 44852	SKU 44853
Number of rungs 3 × 8	Number of rungs 3 × 10	Number of rungs 3 × 12
Overall length, extended 5.25 m	Overall length, extended 6.65 m	Overall length, extended 8.33 m
Overall length, retracted 2.41 m	Overall length, retracted 2.97 m	Overall length, retracted 3.53 m
Stile depth 68 mm	Stile depth 73 mm	Stile depth 85 mm
Transport dimensions 2.410 mm × 500 mm × 170 mm	Transport dimensions 2.970 mm × 500 mm × 190 mm	Transport dimensions 3.530 mm × 500 mm × 190 mm
Weight 15.3 kg	Weight 19.2 kg	Weight 24.2 kg
Wide crosspiece 0.9 m	Wide crosspiece 1.1 m	Wide crosspiece 1.2 m
Working height 5.95 m	Working height 7.25 m	Working height 8.8 m
SKU 44854		
Number of rungs 3 × 14		



ZARGES

Overall length, extended

9.45 m

Overall length, retracted

4.09 m

Stile depth

85 mm

Transport dimensions

4.090 mm × 500 mm × 190 mm

Weight

36 kg

Wide crosspiece

1.2 m

Working height

9.9 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

www.zarges.com

zarges@zarges.de

Effective
2/12/2026

Subject to change or error.

3/3