DATA SHEET

PaxTower 1T

The compact, one-click folding scaffold unit for the discerning skilled worker. Quick to set up, sturdy, and safe to work on.















PRODUCT DESCRIPTION

- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- In accordance with the new EN 1004-1 standard – except for base package 53510.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/ m²) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42794) to allow for height adjustment.
- Stile and rung diameter 45 mm.

PRODUCT FEATURES

Property	Value
Claw type	automatic
Fits through doorways	Yes
Height-adjustable castors:	No
Platform length	1.8 m

Property	Value
Platform length	1.8 m
Platform size	0,6m × 1,8m
Platform width	0.6 m
Rung diameter	45 mm
Scaffolding class	3 (= 200 kg/m²)
Standards	EN 1004-1
Stile diameter	45 mm
Warranty	10 years
Wheel diameter	125 mm
Width scaffolding	0.72 m

PRODUCT VARIANTS

	53511	53512	53513	53514	53515	53516
Overall height	1.65 m	2.65 m	3.65 m	4.65 m	5.65 m	6.65 m
Platform height	0.55 m	1.55 m	2.55 m	3.55 m	4.55 m	5.55 m
Transport dimensions	1.950 mm × 750 mm × 400 mm	2.150 mm × 750 mm × 700 mm	2.150 mm × 750 mm × 750 mm	2.150 mm × 750 mm × 950 mm	2.150 mm × 750 mm × 1.050 mm	2.150 mm × 750 mm × 1.300 mm
Weight	38.3 kg	68 kg	78 kg	95.3 kg	111.2 kg	130.4 kg
Working height	2.55 m	3.55 m	4.55 m	5.55 m	6.55 m	7.55 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 1



PaxTower S-PLUS 1T and 1T packs
SKU 53550 · 53551 · 53552 · +4

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/11/2026
Subject to change or error.