

Everest Plus 2E

Stay safe at the top. The extension ladder features 80 mm deep treads instead of rungs on the upper ladder.

Product description

- Stand safely at the top. The extension ladder with treads instead of rungs on the upper ladder.
- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- The upper ladder is fitted with plastic wheels to prevent damage to walls.
- Height adjustment in increments of 280 mm.
- Upper ladder fitted with plastic wall wheels.
- Locks safely by means of hooks with lift-off retainer.
- Ladder width: 420 mm.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
External width of lower ladder	420 mm



Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	73 mm
Warranty	10 years
Wheels	Rubber

Product variants

	40467	40468	40469
Number of rungs	2 x 8	2 x 10	2 x 12
Overall length, extended	4.2 m	5.32 m	6.44 m
Overall length, retracted	2.52 m	3.08 m	3.64 m
Transport dimensions	approx. 2.520 mm x approx. 420 mm x approx. 200 mm	approx. 3.080 mm x approx. 420 mm x approx. 200 mm	approx. 3.640 mm x approx. 420 mm x approx. 200 mm
Weight	11.5 kg	13.9 kg	17 kg
Wide crosspiece	0.9 m	1 m	1.1 m
Working height	4.9 m	5.95 m	7 m

ZARGES GmbH Zargesstraße 7 82362 Weilheim	Tel: +49 (0)881-687-100	www.zarges.com
	Fax: +49 (0)881-687-500	Effective 6/26/2026
	zarges@zarges.de	Subject to change or error.