

Everest Plus 2E

Better footing at the top. The push-up ladder with 80 mm deep treads instead of rungs.

Product description

- Provides a safe place to stand for work at height.
The push-up ladder with treads instead of rungs.
- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- The upper ladder is fitted with plastic wheels to prevent damage to walls.
- Height adjustment in increments of 280 mm.
- Upper ladder fitted with plastic wall wheels.
- Locks safely by means of hooks with lift-off retainer.
- Ladder width: 420 mm.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 420 mm	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread	Standards	Stile depth	Warranty	Wheels

265 mm

EN 131 professional

73 mm

10 years

Rubber

Product variants

SKU	SKU	SKU
40467	40468	40469
Number of rungs	Number of rungs	Number of rungs
2 × 8	2 × 10	2 × 12
Overall length, extended	Overall length, extended	Overall length, extended
4.2 m	5.32 m	6.44 m
Overall length, retracted	Overall length, retracted	Overall length, retracted
2.52 m	3.08 m	3.64 m
Transport dimensions	Transport dimensions	Transport dimensions
approx. 2.520 mm × approx. 420 mm × approx. 200 mm	approx. 3.080 mm × approx. 420 mm × approx. 200 mm	approx. 3.640 mm × approx. 420 mm × approx. 200 mm
Weight	Weight	Weight
11.5 kg	13.9 kg	17 kg
Wide crosspiece	Wide crosspiece	Wide crosspiece
0.9 m	1 m	1.1 m
Working height	Working height	Working height
4.9 m	5.95 m	7 m