

Everest Plus 2E

Better footing at the top. The push-up ladder with 80 mm deep treads instead of rungs.

Product description

- Provides a safe place to stand for work at height. The push-up ladder with treads instead of rungs.
- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- The upper ladder is fitted with plastic wheels to prevent damage to walls.
- Height adjustment in increments of 280 mm.
- Upper ladder fitted with plastic wall wheels.
- Locks safely by means of hooks with lift-off retainer.
- Ladder width: 420 mm.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 420 mm	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread	Standards	Stile depth	Warranty	Wheels



265 mm	EN 131 professional	73 mm	10 years	Rubber
certification-mark-pf TÜV-SÜD				

Product variants

SKU 40467	SKU 40468	SKU 40469
Number of rungs 2 × 8	Number of rungs 2 × 10	Number of rungs 2 × 12
Overall length, extended 4.2 m	Overall length, extended 5.32 m	Overall length, extended 6.44 m
Overall length, retracted 2.52 m	Overall length, retracted 3.08 m	Overall length, retracted 3.64 m
Transport dimensions approx. 2.520 mm × approx. 420 mm × approx. 200 mm	Transport dimensions approx. 3.080 mm × approx. 420 mm × approx. 200 mm	Transport dimensions approx. 3.640 mm × approx. 420 mm × approx. 200 mm
Weight 11.5 kg	Weight 13.9 kg	Weight 17 kg
Wide crosspiece 0.9 m	Wide crosspiece 1 m	Wide crosspiece 1.1 m
Working height 4.9 m	Working height 5.95 m	Working height 7 m