

AXIC-I

Simple lanyard with an elastic arm in accordance with EN 354:2010 and an energy absorber in accordance with EN 355:2002. The length is adjustable and can be set between 1.40 m and 1.80 m. Equipped with a rebar hook.

Product description

- Simple lanyard in accordance with EN 354:2010 with an energy absorber in accordance with EN 355:2002.
- Adjustable length between 1.40 and 1.80 m.
- Equipped with rebar hooks.
- Suitable for people weighing up to 150 kg.
- ZmartCheck - provides quick access to security-relevant information.
- DIN 19427
- Suitable for sharp edges, RfU 11.074.



Product features

Carabiner Anchor Point Page	Aluminum rebar hook
Fabric	Polyester
Length Range	1,4-1,8 m
Maximum length	1.8 m
Maximum service life	10 J
Maximum user weight	150 kg
Minimum length	1.4 m
Smart Check	Yes



Suitable for edges	Yes
energy absorber	Yes

Product variants

	47808	47859	47862
Carabiner Full Body Harness Page	Aluminum snap carabiner	Twist-lock	Tri-lock
Standards	EN 354,EN 355,DIN 19427	EN 354,EN 355,DIN 19427	EN 354,EN 355,DIN 19427
Weight	1.1 kg	1.15 kg	1.15 kg

ZARGES GmbH Zargesstraße 7 82362 Weilheim	Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 zarges@zarges.de	www.zarges.com Effective 6/27/2026 Subject to change or error.
---	--	--