

AXIC-Y

Double lanyard with elastic arms in accordance with EN 354:2010 and an integrated energy absorber in accordance with EN 355:2002. The integrated O-ring prevents distortion of the arms during use. The length is adjustable and can be varied between 1.40 m and 1.80 m. The lanyard is available with either carabiners or rebar hooks.



Product description

- Double lanyard in accordance with EN 354:2010 with an energy absorber in accordance with EN 355:2002.
- Adjustable length between 1.40 and 1.80 m.
- Equipped with carabiners or rebar hooks.
- Thanks to its round shape, the central RING eyelet allows for optimal positioning to prevent distortion.
- Suitable for people weighing up to 150 kg.
- ZmartCheck - provides quick access to security-relevant information.
- Suitable for sharp edges, RfU 11.074.

Product features

Length Range	1,4-1,8 m
Maximum length	1.8 m
Maximum service life	10 J
Maximum user weight	150 kg
Minimum length	1.4 m
Smart Check	Yes



Suitable for edges	Yes
energy absorber	Yes

Product variants

	47809	47860	47863	47810	47861	47864
Carabiner Anchor Point Page	Aluminum rebar hook	Aluminum rebar hook	Aluminum rebar hook	Aluminum snap carabiner	Aluminum snap carabiner	Aluminum snap carabiner
Carabiner Full Body Harness Page	Aluminum snap carabiner	Twist-lock	Tri-lock	Aluminum snap carabiner	Twist-lock	Tri-lock
Standards	EN 354,EN 355	EN 354,EN 355	EN 354,EN 355	EN 354,EN 355	EN 354,EN 355	EN 354,EN 355
Weight	1.8 kg	1.85 kg	1.85 kg	1.1 kg	1.15 kg	1.15 kg

	47867	47877
Carabiner Anchor Point Page	Maxi Rebar hook	Steel rebar hook
Carabiner Full Body Harness Page	Aluminum snap carabiner	Aluminum snap carabiner
Standards	EN 354,EN 355	EN 354,EN 355
Weight	1.9 kg	1.9 kg

ZARGES GmbH Zargesstraße 7 82362 Weilheim	Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 zarges@zarges.de	www.zarges.com Effective 5/13/2026 Subject to change or error.
---	--	--