

## AXIC-Y

Double lanyard with elastic arms in accordance with EN 354:2010 and an integrated energy absorber in accordance with EN 355:2002. The integrated O-ring prevents distortion of the arms during use. The length is adjustable and can be varied between 1.40 m and 1.80 m. The lanyard is available with either carabiners or rebar hooks.



### Product description

- Double lanyard in accordance with EN 354:2010 with an energy absorber in accordance with EN 355:2002.
- Adjustable length between 1.40 and 1.80 m.
- Equipped with carabiners or rebar hooks.
- Thanks to its round shape, the central RING eyelet allows for optimal positioning to prevent distortion.
- Suitable for people weighing up to 150 kg.
- ZmartCheck - provides quick access to security-relevant information.
- Suitable for sharp edges, RfU 11.074.

### Product features

|                      |           |
|----------------------|-----------|
| Length Range         | 1,4-1,8 m |
| Maximum length       | 1.8 m     |
| Maximum service life | 10 J      |
| Maximum user weight  | 150 kg    |
| Minimum length       | 1.4 m     |
| Smart Check          | Yes       |



|                    |     |
|--------------------|-----|
| Suitable for edges | Yes |
| energy absorber    | Yes |

## Product variants

|                                  | 47809                   | 47860               | 47863               | 47810                   | 47861                   | 47864                   |
|----------------------------------|-------------------------|---------------------|---------------------|-------------------------|-------------------------|-------------------------|
| Carabiner Anchor Point Page      | Aluminum rebar hook     | Aluminum rebar hook | Aluminum rebar hook | Aluminum snap carabiner | Aluminum snap carabiner | Aluminum snap carabiner |
| Carabiner Full Body Harness Page | Aluminum snap carabiner | Twist-lock          | Tri-lock            | Aluminum snap carabiner | Twist-lock              | Tri-lock                |
| Standards                        | EN 354,EN 355           | EN 354,EN 355       | EN 354,EN 355       | EN 354,EN 355           | EN 354,EN 355           | EN 354,EN 355           |
| Weight                           | 1.8 kg                  | 1.85 kg             | 1.85 kg             | 1.1 kg                  | 1.15 kg                 | 1.15 kg                 |

|                                  | 47867                   | 47877                   |
|----------------------------------|-------------------------|-------------------------|
| Carabiner Anchor Point Page      | Maxi Rebar hook         | Steel rebar hook        |
| Carabiner Full Body Harness Page | Aluminum snap carabiner | Aluminum snap carabiner |
| Standards                        | EN 354,EN 355           | EN 354,EN 355           |
| Weight                           | 1.9 kg                  | 1.9 kg                  |

|   |  |  |
|---|--|--|
| ZARGES GmbH<br>Zargesstraße 7<br>82362 Weilheim | Tel: +49 (0)881-687-100<br>Fax: +49 (0)881-687-500<br>zarges@zarges.de | www.zarges.com<br>Effective 6/27/2026<br>Subject to change or error. |
|---|--|--|