

XLstep P

Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimum stability thanks to rigid locking bar on both sides.
- Double-sided access.
- Abrasion-resistant, anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183



Product features

Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	riveted
Load capacity	150 kg
Material	Anodised aluminium
Pitch rung/tread	250 mm
Platform length	300 mm
Platform width	400 mm



Standards	EN 14183
Stile depth	48 mm
Tread depth	92 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	40101	40102	40103
Base	0,64 m × 0,6 m	0,82 m × 0,68 m	0,99 m × 0,76 m
Number of treads	2 × 2	2 × 3	2 × 4
Overall base width	0.6 m	0.68 m	0.76 m
Platform height	0.49 m	0.74 m	0.99 m
Transport dimensions	approx. 580 mm × approx. 600 mm × approx. 290 mm	approx. 840 mm × approx. 680 mm × approx. 290 mm	approx. 1.105 mm × approx. 760 mm × approx. 290 mm
Weight	4.7 kg	6.1 kg	7.8 kg
Working height	2.49 m	2.74 m	2.99 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 4/16/2026

Subject to change or error.