



# GRP Swingback Step - 300514

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

## Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti-splay mechanism	Rigid locking bar
Base	0,85 m × 0,47 m
Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg



Material	Aluminium / plastic
Number of rungs, incl. platform	4
Overall base width	0.47 m
Overall length	1.24 m
Standards	EN 131 professional
Stile depth	80 mm
Stile depth	48 mm
Stile depth steps/back stay	80mm / 48mm
Storage tray	Plastic
Transport dimensions	approx. 1.240 mm × approx. 470 mm × approx. 160 mm
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	298 mm
Vertical ladder height	1.12 m
Warranty	10 years
Weight	6.69 kg

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 27/6/2026  
 Subject to change or error.