



GRP Swingback Step - 300515

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|--|-------------------|
| Anti-splay mechanism | Rigid locking bar |
| Base | 1,04 m × 0,51 m |
| Connection between stiles and rungs/stiles | riveted |
| Load capacity | max. 150 kg |



| | |
|---|--|
| Material | Aluminium / plastic |
| Number of rungs, incl. platform | 5 |
| Overall base width | 0.51 m |
| Overall length | 1.54 m |
| Standards | EN 131 professional |
| Stile depth | 80 mm |
| Stile depth | 48 mm |
| Stile depth steps/back stay | 80mm / 48mm |
| Storage tray | Plastic |
| Transport dimensions | approx. 1.540 mm × approx. 510 mm × approx. 160 mm |
| Tread depth | 80 mm |
| Type of rungs/treads | serrated |
| Vertical distance between each rung/tread | 298 mm |
| Vertical ladder height | 1.39 m |
| Warranty | 10 years |
| Weight | 7.6 kg |

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 27/6/2026
 Subject to change or error.