



# GRP Swingback Step - 300515

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

## Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti-splay mechanism <b>Rigid locking bar</b>	Base <b>1,04 m × 0,51 m</b>	Connection between stiles and rungs/stiles <b>riveted</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium / plastic</b>
Number of rungs, incl.	Overall base width	Overall length	Standards	Stile depth



platform <b>5</b>	<b>0.51 m</b>	<b>1.54 m</b>	<b>EN 131 professional</b>	<b>80 mm</b>
Stile depth <b>48 mm</b>	Stile depth steps/back stay <b>80mm / 48mm</b>	Storage tray <b>Plastic</b>	Transport dimensions <b>approx. 1.540 mm × approx. 510 mm × approx. 160 mm</b>	Tread depth <b>80 mm</b>
Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>298 mm</b>	Vertical ladder height <b>1.39 m</b>	Warranty <b>10 years</b>	Weight <b>7.6 kg</b>