



# GRP Swingback Step - 300515

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

## Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.



## Hints and special features

Complies with EN 131 Professional.

## Product features


|  |                                |  |                                     |  |
|--|--------------------------------|--|-------------------------------------|--|
| Anti-splay mechanism<br><b>Rigid locking bar</b> | Base<br><b>1,04 m x 0,51 m</b> | Connection between stiles and rungs/stiles<br><b>riveted</b> | Load capacity<br><b>max. 150 kg</b> | Material<br><b>Aluminium / plastic</b> |
| Number of rungs, incl.                           | Overall base width             | Overall length   | Standards                           | Stile depth                            |



**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/grp-swingback-step-300515>



|   |  |   |   |                             |
|---|--|---|---|-----------------------------|
| platform<br><b>5</b>                    | <b>0.51 m</b>  | <b>1.54 m</b>                           | <b>EN 131 professional</b>  | <b>80 mm</b>                |
| Stile depth<br><b>48 mm</b>             | Stile depth steps/back stay<br><b>80mm / 48mm</b>          | Storage tray<br><b>Plastic</b>          | Transport dimensions<br><b>approx. 1.540 mm x approx. 510 mm x approx. 160 mm</b> | Tread depth<br><b>80 mm</b> |
| Type of rungs/treads<br><b>serrated</b> | Vertical distance between each rung/tread<br><b>298 mm</b> | Vertical ladder height<br><b>1.39 m</b> | Warranty<br><b>10 years</b>   | Weight<br><b>7.6 kg</b>     |