



GRP Swingback Step - 300516

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|--|--------------------------------|--|-------------------------------------|--|
| Anti-splay mechanism Rigid locking bar | Base 1,22 m × 0,54 m | Connection between stiles and rungs/stiles riveted | Load capacity max. 150 kg | Material Aluminium / plastic |
| Number of rungs, incl. | Overall base width | Overall length | Standards | Stile depth |



| | | | | |
|---|--|---|---|-----------------------------|
| platform 6 | 0.54 m | 1.84 m | EN 131 professional | 80 mm |
| Stile depth 48 mm | Stile depth steps/back stay 80mm / 48mm | Storage tray Plastic | Transport dimensions approx. 1.840 mm × approx. 540 mm × approx. 160 mm | Tread depth 80 mm |
| Type of rungs/treads serrated | Vertical distance between each rung/tread 298 mm | Vertical ladder height 1.67 m | Warranty 10 years | Weight 8.7 kg |