



GRP Swingback Step - 300520

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.




Hints and special features

Complies with EN 131 Professional.

Product features

Anti-splay mechanism Rigid locking bar	Base 1,97 m × 0,69 m	Connection between stiles and rungs/stiles riveted	Load capacity max. 150 kg	Material Aluminium / plastic
Number of rungs, incl.	Overall base width	Overall length	Standards	Stile depth



platform 10	0.69 m	3.02 m	EN 131 professional	80 mm
Stile depth 48 mm	Stile depth steps/back stay 80mm / 48mm	Storage tray Plastic	Transport dimensions approx. 3.020 mm × approx. 690 mm × approx. 160 mm	Tread depth 80 mm
Type of rungs/treads serrated	Vertical distance between each rung/tread 298 mm	Vertical ladder height 2.79 m	Warranty 10 years	Weight 16.46 kg