





K 470 universal container, IP 65 - 366206

TÜV Süd-certified box with pressure equalization valve—ideal for all applications requiring enhanced protection against moisture, water spray, and dust.

Product description

- TÜV Süd-certified box with pressure equalization valve—ideal for all applications requiring enhanced protection against moisture, water spray, and dust.
- IP 65 protection rating in accordance with DIN EN 60529, achieved by a foamed gasket integrated into the cover.
- 22 standard sizes of the K 470 are available from stock in IP65. The three variants with lengths of 1,400 mm or more also offer enhanced protection thanks to an optimized seal and pressure-equalizing valve, but do not fully meet the requirements of protection class IP65.
- Also available with approval for the transportation of hazardous goods.
- Extra-thick aluminium sheets (1.5 mm) are used on all K 470 containers with base dimensions 750 x 550 mm and above.
- Automatic pressure-equalizing diaphragm.
- TÜV SÜD-certified.
- Available for most K 470 models.



Hints and special features

UN approval for the transportation of hazardous



goods possible at additional charge.

Clearance dimensions approx. 30 mm less than inside dimensions (length and width). Special sizes on request.

Product features

Certification	TÜV Süd - IP 65
Colour of the stacking corners	Natural aluminium
Corner beading	Yes
Fasteners	Comfort fasteners
Integrated wheels	No
Internal dimensions L x W x H	550 mm x 350 mm x 380 mm
Material	aluminium
Material of the stacking corners	aluminium
Max. gross weight dangerous goods permission	75 kg
Number of handles	2
Outside dimensions max. L x W x H	600 mm x 400 mm x 410 mm
Peripheral beading	Yes
Protection class	IP65:
Seal	foamed lid seal
Stacking corners	Yes
Volume	73 l
Warranty	10 years
Weight	5.3 kg



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 26/6/2026
Subject to change or error.