



AFA P - 40033

The basic steps with low weight, high stability and convenient standing area.

Product description

- The basic steps with low weight, high stability and convenient standing area.
- High-strength, welded tubular aluminium construction ensures stability and long service life.
- 200 mm deep steps made of non-slip ribbed aluminium sheet.
- 350 x 577 mm standing platform braced by a cross-strut.
- Maximum stability thanks to a wide standing surface.
- Stile ends with plastic edge finish.



Hints and special features

Self-locking sprung castors available as an accessory from two steps upwards. Handrail available as an accessory from three steps upwards.

Complies with EN 14 183

Product features

Base	0,87 m × 0,69 m
Coating	natural
Connection between stiles and rungs/stiles	welded
Load capacity	max. 150 kg



Material	aluminium
Number of rungs, incl. platform	3
Platform height	0.6 m
Platform length	350 mm
Platform width	577 mm
Standards	EN 14183
Transport dimensions	692 mm × 871 mm × 600 mm
Tread depth	200 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	200 mm
Warranty	10 years
Weight	7.8 kg
Working height	2.6 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 31/3/2026
 Subject to change or error.