



## AFA P - 40033

The basic steps with low weight, high stability and convenient standing area.

### Product description

- The basic steps with low weight, high stability and convenient standing area.
- High-strength, welded tubular aluminium construction ensures stability and long service life.
- 200 mm deep steps made of non-slip ribbed aluminium sheet.
- 350 x 577 mm standing platform braced by a cross-strut.
- Maximum stability thanks to a wide standing surface.
- Stile ends with plastic edge finish.



### Hints and special features

Self-locking sprung castors available as an accessory from two steps upwards. Handrail available as an accessory from three steps upwards.

Complies with EN 14 183

### Product features

Base <b>0,87 m × 0,69 m</b>	Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>welded</b>	Load capacity <b>max. 150 kg</b>	Material <b>aluminium</b>
Number of rungs, incl. platform	Platform height	Platform length	Platform width	Standards



<b>3</b>	<b>0.6 m</b>	<b>350 mm</b>	<b>577 mm</b>	<b>EN 14183</b>
Transport dimensions <b>692 mm × 871 mm × 600 mm</b>	Tread depth <b>200 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/ tread <b>200 mm</b>	Warranty <b>10 years</b>
Weight <b>7.8 kg</b>	Working height <b>2.6 m</b>			