



## AFA P - 40035

The basic steps with low weight, high stability and convenient standing area.

### Product description

- The basic steps with low weight, high stability and convenient standing area.
- High-strength, welded tubular aluminium construction ensures stability and long service life.
- 200 mm deep steps made of non-slip ribbed aluminium sheet.
- 350 x 577 mm standing platform braced by a cross-strut.
- Maximum stability thanks to a wide standing surface.
- Stile ends with plastic edge finish.



### Hints and special features

Self-locking sprung castors available as an accessory from two steps upwards. Handrail available as an accessory from three steps upwards.

Complies with EN 14 183

### Product features

Base	1,35 m × 0,73 m
Coating	natural
Connection between stiles and rungs/stiles	welded
Load capacity	max. 150 kg



Material	aluminium
Number of rungs, incl. platform	5
Platform height	0.99 m
Platform length	350 mm
Platform width	577 mm
Standards	EN 14183
Transport dimensions	734 mm × 1.336 mm × 1.000 mm
Tread depth	200 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	200 mm
Warranty	10 years
Weight	13.5 kg
Working height	3 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 30/6/2026  
 Subject to change or error.