



AFA P - 40035

The basic steps with low weight, high stability and convenient standing area.

Product description

- The basic steps with low weight, high stability and convenient standing area.
- High-strength, welded tubular aluminium construction ensures stability and long service life.
- 200 mm deep steps made of non-slip ribbed aluminium sheet.
- 350 x 577 mm standing platform braced by a cross-strut.
- Maximum stability thanks to a wide standing surface.
- Stile ends with plastic edge finish.



Hints and special features

Self-locking sprung castors available as an accessory from two steps upwards. Handrail available as an accessory from three steps upwards.

Complies with EN 14 183

Product features

Base 1,35 m x 0,73 m	Coating natural	Connection between stiles and rungs/stiles welded	Load capacity max. 150 kg	Material aluminium
Number of rungs, incl. platform	Platform height	Platform length	Platform width	Standards



ZARGES

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/afa-p-40035>



5	0.99 m	350 mm	577 mm	EN 14183
Transport dimensions 734 mm × 1.336 mm × 1.000 mm	Tread depth 200 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 200 mm	Warranty 10 years
Weight 13.5 kg	Working height 3 m			