



Fuelling ladder with 6 treads - 40051

The universal platform ladder for all kinds of demanding applications. You can also use this ladder as a refuelling ladder to help you get work done quickly and safely.

Product description

- The universal platform ladder for all kinds of demanding applications. You can also use this ladder as a refuelling ladder to help you get work done quickly and safely.
- Our ladder is equipped with two removable mounts for securely holding underwing refuelling nozzles on the ladder's access section.
- A stabiliser on the ladder's support section ensures safe standing. Also available in other widths.
- The spacious platform (500x450mm) made of steel grating ensures maximum secure footing thanks to its R13 slip-resistance rating and design that allows liquids to drain off.
- Two wheels on the access section ensure easy ladder operation. The wheels can also be attached to the support section.
- Improved safety even when working with oily substances or outdoors in icy or wet conditions.
- Large, serrated-surface standing platform for safe and comfortable working.
- Easily collapsible for transport and storage.





- 80 mm deep treads with R13 surface and perforations to drain fluids fast.
- All-round railings.
- Wide horizontal stabiliser bar.

Product features

Anti-splay mechanism Belt strap	Coating natural	Connection between stiles and rungs/stiles flanged	Load capacity max. 150 kg	Material Natural aluminium
Number of rungs, incl. platform 6	Overall base width 1400 mm	Platform height 1.6 m	Platform length 500 mm	Platform width 450 mm
Standards EN 131-7	Stile depth 73 mm	Transport dimensions 2.550 mm × 1.450 mm × 400 mm	Tread depth 80 mm	Type of rungs/treads R13 tread
Vertical distance between each rung/tread 265 mm	Warranty 10 years	Weight 20 kg	Wide crosspiece 1.4 m	Working height 3.6 m
non-static Yes				