



# Access steps - 40055234

Stationary access to buildings and machines.

## Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Hook-on cantilevers, set of hooks and support bracket to integrate the product as detachable in a fixing.
- Plastic support plate for floor bracket for fast removal of product.
- Standard applied: DIN EN ISO 14122.



## Hints and special features

Standard applied: DIN EN ISO 14122.

## Product features

|                                  |                                     |                                      |                               |                                |
|----------------------------------|-------------------------------------|--------------------------------------|-------------------------------|--------------------------------|
| Inclination<br><b>60 °</b>       | Load capacity<br><b>max. 300 kg</b> | Max. load per tread<br><b>150 kg</b> | Number of treads<br><b>15</b> | Overall span<br><b>2304 mm</b> |
| Standards<br><b>EN ISO 14122</b> | Tread width<br><b>800 mm</b>        | Vertical height<br><b>3750 mm</b>    | Warranty<br><b>10 years</b>   |                                |