



Fuelling ladder with 4 treads - 40098

The universal platform ladder for any heavy-duty application! Or specifically as a refuelling ladder.

Product description

- The universal platform ladder for any heavy-duty application! Or specifically as a refuelling ladder.
- Our ladder is equipped with two removable mounts for securely holding underwing refuelling nozzles on the ladder's access section.
- The crossbar on the ladder's support section ensures stability.
- The spacious platform (450 x 500 mm), made of steel grating with a slip resistance rating of R13, ensures maximum stability.
- Two electrically conductive rollers on the riser provide a simple method for moving the conductors.
- Improved safety even when working with oily substances or outdoors in icy or wet conditions.
- Large, serrated-surface standing platform for safe and comfortable working.
- Easily collapsible for transport and storage.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- All-round railings.
- Wide horizontal stabiliser bar.





Product features

Anti-splay mechanism	Belt strap
Coating	natural
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 150 kg
Material	Natural aluminium
Number of rungs, incl. platform	4
Overall base width	1100 mm
Platform height	1.07 m
Platform length	500 mm
Platform width	450 mm
Standards	EN 131-7
Stile depth	73 mm
Transport dimensions	2.050 mm × 1.200 mm × 400 mm
Tread depth	80 mm
Type of rungs/treads	R13 tread
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	17 kg
Wide crosspiece	1.1 m
Working height	3 m
non-static	Yes



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 30/5/2026
Subject to change or error.