



# XLstep P - 40101

## Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimum stability thanks to rigid locking bar on both sides.
- Double-sided access.
- Wear-resistant, anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



## Hints and special features

Complies with EN 14 183



## Product features

Base <b>0,64 m × 0,6 m</b>	Coating <b>anodised</b>	Connection between stiles and rungs/stiles <b>riveted</b>	Load capacity <b>150 kg</b>	Material <b>Anodised aluminium</b>
Number of treads <b>2</b>	Number of treads <b>2 × 2</b>	Overall base width <b>0.6 m</b>	Platform height <b>0.49 m</b>	Platform length <b>300 mm</b>
Platform width <b>400 mm</b>	Standards <b>EN 14183</b>	Stile depth <b>48 mm</b>	Transport dimensions <b>approx. 580 mm × approx. 600 mm × approx. 290 mm</b>	Tread depth <b>92 mm</b>



Type of rungs/treads  
**serrated**

Vertical distance  
between each rung/  
tread  
**250 mm**

Warranty  
**10 years**

Weight  
**4.7 kg**

Working height  
**2.49 m**

certification-mark-pf  
**TÜV-SÜD**