



XLstep P - 40102

Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimum stability thanks to rigid locking bar on both sides.
- Double-sided access.
- Wear-resistant, anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183



Product features

| | | | | |
|---------------------------------|----------------------------------|--|---|---------------------------------------|
| Base 0,82 m × 0,68 m | Coating anodised | Connection between stiles and rungs/stiles riveted | Load capacity 150 kg | Material Anodised aluminium |
| Number of treads 3 | Number of treads 2 × 3 | Overall base width 0.68 m | Platform height 0.74 m | Platform length 300 mm |
| Platform width 400 mm | Standards EN 14183 | Stile depth 48 mm | Transport dimensions approx. 840 mm × approx. 680 mm × approx. 290 mm | Tread depth 92 mm |



| | | | | |
|---|---|---------------------------------|-----------------------------|-------------------------------------|
| Type of rungs/treads serrated | Vertical distance between each rung/ tread 250 mm | Warranty 10 years | Weight 6.1 kg | Working height 2.74 m |
| certification-mark-pf TÜV-SÜD | | | | |