



# XLstep P - 40103

## Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimum stability thanks to rigid locking bar on both sides.
- Double-sided access.
- Wear-resistant, anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.




## Hints and special features

Complies with EN 14 183



## Product features

Base <b>0,99 m × 0,76 m</b>	Coating <b>anodised</b>	Connection between stiles and rungs/stiles <b>riveted</b>	Load capacity <b>150 kg</b>	Material <b>Anodised aluminium</b>
Number of treads <b>4</b>	Number of treads <b>2 × 4</b>	Overall base width <b>0.76 m</b>	Platform height <b>0.99 m</b>	Platform length <b>300 mm</b>
Platform width <b>400 mm</b>	Standards <b>EN 14183</b>	Stile depth <b>48 mm</b>	Transport dimensions <b>approx. 1.105 mm × approx. 760 mm × approx. 290 mm</b>	Tread depth <b>92 mm</b>



Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/ tread  <b>250 mm</b>	Warranty  <b>10 years</b>	Weight  <b>7.8 kg</b>	Working height  <b>2.99 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				