



RCstep BP - 40138

Product description

- Platform size approx. 600 x 300 mm
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Double-sided access.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183

Product features

| | |
|--|--------------------|
| Base | 0,82 m × 0,88 m |
| Coating | anodised |
| Connection between stiles and rungs/stiles | riveted |
| Load capacity | 150 kg |
| Material | Anodised aluminium |
| Number of treads | 3 |
| Number of treads | 2 × 3 |
| Overall base width | 0.88 m |
| Platform height | 0.74 m |



| | |
|---|--|
| Platform length | 300 mm |
| Platform width | 600 mm |
| Standards | EN 14183 |
| Stile depth | 48 mm |
| Transport dimensions | approx. 840 mm × approx. 880 mm × approx. 290 mm |
| Tread depth | 92 mm |
| Type of rungs/treads | RC tread |
| Vertical distance between each rung/tread | 250 mm |
| Warranty | 10 years |
| Weight | 7.4 kg |
| Working height | 2.74 m |

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 2/7/2026
 Subject to change or error.